



SXS GEAR

HIGH PERFORMANCE GEAR OIL

DESCRIPTION:

Mineral-based gear oil specifically formulated for hypoid-type differentials found in modern side-by-side (SXS) vehicles. Robust, shear-stable formulation can also be used in side-by-side transmissions and gear cases requiring SAE 90wt gear oil. Proprietary shape combines the finest mineral base stocks with industry leading extreme pressure and anti-wear additives to ensure hardware protection and smooth shifting. Exceeds the requirements of API GL-5.

FEATURES & BENEFITS:

- Formulated specifically for use in modern side-by-side vehicles
- Superior protection from wear, pitting and spalling
- Shear stable formula maintains viscosity and ensures smooth shifting
- Surface-active chemistry keeps surfaces free of corrosion, deposits and wear
- Exceeds API GL-5 specifications

APPLICATIONS:

For hypoid-type differentials found in modern SXS, ATV and UTV. Can be used in SXS, ATV and UTV transmissions and gear cases recommending SAE 90wt gear oil.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	80W-90
APPEARANCE	VISUAL	Amber
VISCOSITY @ 40°C (cSt)	D445	171.7
VISCOSITY @ 100°C (cSt)	D445	16.3
VISCOSITY INDEX	D2270	99
FLASH POINT (°C)	D92	397
POUR POINT (°C)	D97	-27
DENSITY @ 15 °C (g/ml)	D4052	-

EXPERIENCE THE DIFFERENCE

Made In The USA