

CHAIN CASE LUBE

100% SYNTHETIC CHAIN CASE LUBRICANT

DESCRIPTION:

Full synthetic chain case lubricant specifically formulated to maintain exceptional flow in extreme cold temperatures. Robust, shear-stable formulation combines high quality synthetic base stocks with industry leading extreme pressure and anti-wear additives to ensure maximum protection for highly loaded chains and sprockets. Advanced additive system ensures protection from oxidation and corrosion.

FEATURES & BENEFITS:

- Formulated to maintain exceptional flow in extreme cold
- Shear stable formula maintains viscosity and minimizes chain and sprocket wear
- Robust anti-wear and extreme pressure chemistries provide protection under high loads
- Advanced additive system keeps surfaces free of corrosion and minimizes oxidation
- Extends chain life by minimizing stretch and wear

APPLICATIONS:

For all snowmobiles and ATVs with enclosed chain cases. Can be used in ATV, side-by-side and UTV differentials or transmissions recommending a 140wt gear oil.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	75W-140
APPEARANCE	VISUAL	Amber
VISCOSITY @ 40°C (cSt)	D445	163.0
VISCOSITY @ 100°C (cSt)	D445	26.5
VISCOSITY INDEX	D2270	199
FLASH POINT (°C)	D92	204
POUR POINT (°C)	D97	-42
DENSITY @ 15 °C (g/ml)	D4052	-